TEST REPORT

of the

Julius Kühn-Institut

Federal Research Institute
for Cultivated Plants, Braunschweig

Hollow cone nozzle ASJ HCA 80-04
(Ceramics, plastic-coated, red)

Approved for spraying orchards and vineyards

Applicant and Manufacturer
ASJ Spray-Jet
Via Busca 101
12044 CENTALLO (CN) ITALY
ITALIEN

Approved on
1 August 2017

Institut for Application Technique in Plant Protection DOI: 10.5073/AT.2017.G2012
Messeweg 11-12, 38104 Braunschweig - GERMANY

Assessment

The air-injection hollow cone nozzle ASJ HCA 80-04 (ceramics, plastic-coated, red) was tested without additional accessories and is suitable for orchards and vineyards, provided that the following technical requirements are fulfilled:

1. Installation in nozzle tubes with sufficient and a steady amount of liquid flow,

2. Spray pressure – measured in front of the nozzle – between 3.0 and 20.0 bar; liquid volume flow per nozzle as stated in table below.

Suitable precautions should be taken to assure that the nozzles do not get blocked up or drip when in use. The dimensions of the nozzle tip comply with standard ISO 8169. The colour coding of the nozzle tip comply with standard ISO 10625.

Pressure (bar)	Liquid flow volume without accessories (l/min)	Max. deviation of single nozzle flow from the dosage tables	Droplet spectrum (BCPC-Standard)
3.0	1.66	4.87 %	very coarse
4.0	1.92	-	very coarse
5.0	2.14	4.22 %	very coarse
6.0	2.35	-	coarse
8.0	2.71	-	coarse
10.0	3.03	4.86 %	coarse
12.0	3.32	-	coarse
15.0	3.71	4.08 %	coarse
20.0	4.28	-	-

Basics for testing

The tests were carried out on basis of the Regulations for Testing Plant Protection Equipment (Guideline 2-1.1:2013) and of ISO 5682-1:1999. The requirements of ISO 16119-2:2013 and of JKI-Guideline 1-2.1:2013 were fulfilled.

Field testing:
Obstbauversuchs- und Beratungszentrum
Moorende 53
21635 Jork

Technical testing:
Institut für Anwendungstechnik im Pflanzenschutz des
Julius Kühn-Instituts,
Messeweg 11-12,
38104 Braunschweig

© JKI, May 2018